

# Premium Mineral 25W-60



## STREET & TRACK ENGINE OIL

Nulon Premium Mineral 25W-60 Street & Track Engine Oil is recommended for all large tolerance, high performance 6 and 8 cylinder engines where maximum oil pressure and oil film strength are required.

Nulon Premium Mineral 25W-60 Street & Track Engine Oil is the chosen oil of multiple racing teams as it provides the ultimate engine protection during competition and the high stress conditions found in drag, circuit and 4x4 racing.

### Benefits:

- High zinc formula for extra engine and flat tappet protection
- Viscosity remains stable in high temperature conditions
- Molybdenum Dithiocarbamate (Moly DTC) gives additional high level wear protection and performance
- Provides maximum cold start protection
- Chosen oil of multiple racing teams
- Increased oil film strength helps provide protection against metal to metal contact
- Helps maintain oil pressure under severe conditions
- Enhanced protection for vehicles using E10, E85 and LPG fuels

### Meets or exceeds the following oil industry specifications:

- Society of Automotive Engineering (SAE) : 25W-60
- American Petroleum Institute (API) : SG/CF

Part No	Pack Size	Barcode	Carton QTY
ST25W60-5	5 Litre	9311090 001 077	3



## High Zinc Mineral

Typical Characteristics	
SAE Viscosity Grade	25W-60
Viscosity @ 100°C (cSt) ASTM D445	23.75
Viscosity @ 40°C (cSt) ASTM D445	277.2
Apparent Viscosity by CCS @ -10°C (cP) ASTM D5293	11670
Apparent Viscosity by MRV @ -15°C (cP) ASTM D4684	34540
Viscosity Index ASTM D2270	107
Density @ 15°C (kg/L) ASTM D4052	0.8771
Sulphated Ash (weight %) ASTM D874	0.808
Total Base Number (mg KOH/g) ASTM D2896	6.50
Pour Point (°C) ASTM D97	-15
Flash Point (°C) ASTM D92	244
Zinc (weight %) ASTM D5185	0.140

