

The Nipple Shop

CONCAVE



STRAIGHT



45°ANGLE

THREAD SIZE:	PART NO:
1/8" BSP	D1-2-BP
1/4" BSP	D1-4-BP
4mm OD (drive in)	D1A-4-M
6mm OD (drive in)	D1A-6-M
1/4" OD (drive in)	D1A-4
10mm OD (drive in)	D1A-10-M

THREAD SIZE:	PART NO:
8mm OD (drive in)	D1A-8-M
M10 x 1	D1-10-2-M
M6 x 1	D1-6-2-M
M8 x 1	D1-8-2-M
M8 x 1.25	D1-8-3-M

THREAD SIZE:	PART NO:
1/8" BSP	D2-2-BP
1/4" BSP	D2-4-BP
6mm OD (drive in)	D2A-6-M
1/4" OD (drive in)	D2A-4

ADDITIONAL SIZES AND MATERIALS ARE AVAILABLE

PUSH ON - HOOK NIPPLES



TAT-HEAD -(DOUBLE HEXAGON)

THREAD SIZE:	PART NO:
† 1/8" BSP	TIB-2-BP
† 1/4" BSP	TIB-4-BP
3/8" BSP	TIB-6-BP
3/8" BSF	TIB-6-BF
1/4" BSF	TIB-4-BF
1/8" NPT	TIB-2-NT

THREAD SIZE:	PART NO:
M6 x 1	TIB-6-2-M
M8 x 1	TIB-8-2-M
M8 x 1.25	TIB-8-3-M
M10 x 1	TIB-10-2M
M10 x 1.5	TIB-10-4-M

† AVAILABLE IN BRASS WITH BERYLLIUM BALL AND SPRING



INDUSTRIAL BUTTON HEAD

THREAD SIZE:	PART NO:
M10 x 1	M1-10-2-M
1/8" BSP	M1-2-BP

THREAD SIZE:	PART NO:
1/4" BSP	M1-4-BP
3/8" BSP	M1-6-BP



GIANT BUTTON HEAD

THREAD SIZE:	PART NO:
M16 x 1.5	M22-16-4-M
1/4" BSP	M22-4-BP

THREAD SIZE:	PART NO:
3/8" BSP	M22-6-BP
1/2" BSP	M22-8-BP

ADDITIONAL SIZES AVAILABLE ON REQUEST

LEAK PROOF NIPPLES



THREAD SIZE:
1/8" NPT

ANGLE:
STR

PART NO:
5045

Leak Proof fittings are used when a positive seal is required. They withstand back pressures up to 5000 psi.

NOT SUITABLE AS A CHECK VALVE AGAINST HIGH SUSTAINED BACK PRESSURE.

