

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 1: Identifie	cation of the substance/mixture and of the company/undertaking
1.1 Product identifier	
Product name	Castrol RR 363
Product code	450597-GB13
SDS no.	450597
Product type	Liquid.
1.2 Relevant identified uses	s of the substance or mixture and uses advised against
Use of the substance/ mixture	Brake fluids. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
1.3 Details of the supplier of	of the safety data sheet
Supplier	Castrol (UK) Ltd Wakefield House Pipers Way Swindon Wiltshire SN3 1RE
E-mail address	MSDSadvice@bp.com
1.4 Emergency telephone n	umber
EMERGENCY	Carechem:+44 (0) 1235 239 670 (24 hours)
TELEPHONE NUMBER	
SECTION 2: Hazard	s identification
2.1 Classification of the sub	ostance or mixture
Product definition	Mixture
	D Regulation (EC) No. 1272/2008 [CLP/GHS]
Eye Irrit. 2, H319	
Classification according to	Directive 1999/45/EC [DPD]
The product is classified as	dangerous according to Directive 1999/45/EC and its amendments.
Classification	Xi; R36
See Section 16 for the full te	ext of the R phrases or H statements declared above.
See sections 11 and 12 for r	more detailed information on health effects and symptoms and environmental hazards.
2.2 Label elements	
Hazard pictograms	
Signal word	Warning
Hazard statements	H319 - Causes serious eye irritation.
Precautionary statements	
Prevention	P280 - Wear eye or face protection. P264 - Wash bands thoroughly after bandling

 Response
 P264 - Wash hands thoroughly after handling.

 Response
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

 Storage
 Not applicable.

 Disposal
 Not applicable.

 Hazard symbol or symbols
 Vertice of the symbol of symbols

Product name Castrol RR 363		Product code 450597-	GB13	Page: 1/10	
Version 2	Date of issue 4 February 2014		United Kingdom (UK) (United Kingdom)	Language	ENGLISH

# SECTION 2: Hazards identification

# Indication of danger

Hazardous ingredients	2-(2-(2-butoxyethoxy)ethoxy)ethanol						
Supplemental label elements	Not applicable.						
Special packaging requirements							
Containers to be fitted with child-resistant fastenings	Not applicable.						
Tactile warning of danger	Not applicable.						

# **SECTION 3: Composition/information on ingredients**

Mixture

# Substance/mixture

Polyalkylene glycol ethers / glycols

		<b>Classification</b>			
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
2-(2-(2-butoxyethoxy) ethoxy)ethanol	REACH #: 01-2119475107-38 EC: 205-592-6 CAS: 143-22-6 Index: 603-183-00-0	>=20 - <30	Xi; R41	Eye Dam. 1, H318	[1]
Castor oil, ethoxylated propoxylated	CAS: 72986-44-8	>=5 - <10	Xi; R36/38	Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1]
2-(2-butoxyethoxy)ethanol	REACH #: 01-2119475104-44 EC: 203-961-6 CAS: 112-34-5 Index: 603-096-00-8	>=1 - <5	Xi; R36	Eye Irrit. 2, H319	[1] [2]
2,2' -oxybisethanol	REACH #: 01-2119457857-21 EC: 203-872-2 CAS: 111-46-6 Index: 603-140-00-6	>=3 - <7	Xn; R22	Acute Tox. 4, H302 STOT RE 2, H373 (kidneys) (oral)	[1] [2]

See Section 16 for the full text of the R-phrases declared above.

#### See Section 16 for the full text of the H statements declared above.

#### Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures Eye contact Case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention if irritation develops. **Skin contact** Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops. Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms appear. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by Ingestion mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if symptoms occur. No action shall be taken involving any personal risk or without suitable training. It may be **Protection of first-aiders** dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Product name Castrol RR 363		Product code 450597-GB13		Page: 2/10	
Version 2	Date of issue 4 February 2014		United Kingdom (UK) (United Kingdom)	Language	ENGLISH

# **SECTION 4: First aid measures**

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** Treatment should in general be symptomatic and directed to relieving any effects.

SECTION 5: Firefighting measures						
5.1 Extinguishing media Suitable extinguishing media	🕅 case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.					
Unsuitable extinguishing media	Do not use water jet.					
5.2 Special hazards arising fro	om the substance or mixture					
Hazards from the substance or mixtureIn a fire or if heated, a pressure increase will occur and the container may burst.						
Hazardous combustion products	Combustion products may include the following: carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide)					
5.3 Advice for firefighters						
Special precautions for fire-fighters	Fromptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.					
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.					

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, prote	ctive equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Contact emergency personnel.
For emergency responders	Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for c	containment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	See Section 1 for emergency contact information. See Section 5 for firefighting measures. See Section 8 for information on appropriate personal protective equipment. See Section 12 for environmental precautions. See Section 13 for additional waste treatment information.

Product name Castrol RR 363		Product code 450597-0	GB13	Page: 3/10	
Version 2	Date of issue 4 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH

## **SECTION 7: Handling and storage**

7.1 Processions for safe hand	dling				
7.1 Precautions for safe hand	-				
Protective measures	easures Put on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, s and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reus container. Empty containers retain product residue and can be hazardous.				
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.				
7.2 Conditions for safe storage, including any incompatibilities	from incompat container tight be carefully re	dance with local regulations. Store in a dry, cool and well-ventilated area, away ible materials (see Section 10). Keep away from heat and direct sunlight. Keep ly closed and sealed until ready for use. Containers that have been opened must sealed and kept upright to prevent leakage. Store and use only in equipment/signed for use with this product. Do not store in unlabelled containers.			
Not suitable	Prolonged exposure to elevated temperature				
7.3 Specific end use(s)					
Recommendations	See section 1.	2 and Exposure scenarios in annex, if applicable.			
<b>SECTION 8: Exposu</b>	re controls/p	ersonal protection			
8.1 Control parameters					
Occupational exposure limi	<u>its</u>				
Product/ingred	lient name	Exposure limit values			
2-(2-butoxyethoxy)ethanol		EH40/2005 WELs (United Kingdom (UK)). STEL: 15 ppm 15 minutes. Issued/Revised: 10/2007 TWA: 10 ppm 8 hours. Issued/Revised: 10/2007 TWA: 67.5 mg/m <sup>3</sup> 8 hours. Issued/Revised: 10/2007 STEL: 101.2 mg/m <sup>3</sup> 15 minutes. Issued/Revised: 10/2007			
2,2' -oxybisethanol		EH40/2005 WELs (United Kingdom (UK)).			

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

TWA: 101 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/1997 TWA: 23 ppm 8 hours. Issued/Revised: 1/1997

#### Derived No Effect Level

**Recommended monitoring** 

procedures

No DNELs/DMELs available.

#### Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

**P**rovide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to

Product name Castrol RR 363			Product code 450597-GB13		Page: 4/10	
Version 2	Date of issue 4 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH	

# SECTION 8: Exposure controls/personal protection

Product name Castrol RR 363	Product code 450597-GB13 Page: 5/10
	Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual
	Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
	It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
	For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.
	Glove Thickness:
	Recommended breakthrough times as above. It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.
	Short-term / splash protection:
	replacement regimes are determined and adhered to.
	Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and
	Continuous contact:
	Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:
	Recommended: Butyl gloves. Neoprene gloves. Breakthrough time:
	Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.
	Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).
Hand protection	General Information:
Skin protection	
Eye/face protection	conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions. Safety glasses with side shields.
Respiratory protection	Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.
Individual protection measures	ensure that all items of personal protective equipment are compatible.

Product name Castrol RR 363		Product code 450597	GB13	Page: 5/10		
Version 2	Date of issue 4 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH	

# SECTION 8: Exposure controls/personal protection

	dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
	• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.
Skin and body	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	Liquid.
Colour	Amber.
Odour	Not available.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	240°C (464°F)
Flash point	[Product does not sustain combustion.]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Density	1039 kg/m³ (1.039 g/cm³)
Solubility(ies)	Soluble in water.
Partition coefficient: n-octanol/ water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

### 9.2 Other information

No additional information.

Product name	Castrol RR 363		Product code 450597	-GB13	Page: 6/10
Version 2	Date of issue 4 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH

SECTION 10: Stability and reactivity				
10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.			
10.2 Chemical stability	The product is stable.			
10.3 Possibility of hazardous reactions	Inder normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.			
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).			
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials. Avoid contact with strong oxidizing agents or peroxides.			
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

## Acute toxicity estimates

	Route	ATE value		
Oral		15898.3 mg/kg		
Information on the likely routes of exposure	Routes of entry anticipated: Dermal, Inhalatio	n.		
Potential acute health effect	<u>ts</u>			
Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.			
Ingestion	No known significant effects or critical hazard	S.		
Skin contact	No known significant effects or critical hazard	S.		
Eye contact	No known significant effects or critical hazard	S.		
Symptoms related to the ph	ysical, chemical and toxicological characterist	<u>tics</u>		
Inhalation	May be harmful by inhalation if exposure to va decomposition products occurs.	apour, mists or fumes resulting from thermal		
Ingestion	No specific data.			
Skin contact	No specific data.			
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness			
Delayed and immediate effe	ects and also chronic effects from short and lo	ng term exposure		
Inhalation	Overexposure to the inhalation of airborne dro respiratory tract.	oplets or aerosols may cause irritation of the		
Ingestion	Ingestion of large quantities may cause nause	ea and diarrhoea.		
Skin contact	Prolonged or repeated contact can defat the s	skin and lead to irritation and/or dermatitis.		
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.			
Potential chronic health effe	<u>ects</u>			
General	No known significant effects or critical hazard	S.		
Carcinogenicity	No known significant effects or critical hazard	S.		
Mutagenicity	No known significant effects or critical hazard	S.		
Developmental effects	No known significant effects or critical hazard	S.		
Fertility effects	No known significant effects or critical hazard	S.		

### **SECTION 12: Ecological information**

12.1 Toxicity

**Environmental hazards** 

Not classified as dangerous

## 12.2 Persistence and degradability

Expected to be biodegradable.

#### **12.3 Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil	
Soil/water partition coefficient (K <sub>oc</sub> )	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.

12.5 Results	of	PBT	and	vPvB	assessment
DDT					Not applicab

PBT	Not applicable.
vPvB	Not applicable.

12.6 Other adverse effects

Other ecological information Miscible in water.

## **SECTION 13: Disposal considerations**

=	
13.1 Waste treatment meth	lods
Product	
Methods of disposal	Mhere possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Hazardous waste	Yes.
European waste catalog	ue (EWC)
Waste code	Waste designation
16 01 13*	brake fluids

However, deviation from the i	intended use and/or the presence of any potential contaminants may require an alternative waste
disposal code to be assigned	by the end user.

#### Packaging

Methods of disposal

**Special precautions** 

Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Empty containers represent a fire hazard as they may contain flammable product residues and vapour. Never weld, solder or braze empty containers. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Product nameCastrol RR 363Product code450597-GB13Page: 8/10				
Version 2 Date of	of issue 4 February 2014	Form	at United Kingdom (UK) (United Kingdom)	Language ENGLISH

#### Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)

SECTION 14: Transport information					
Additional information	-	-	-	-	

14.6 Special precautions for Not available. user

#### **SECTION 15: Regulatory information** 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation Substances of very high concern None of the components are listed. **Annex XVII - Restrictions** Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Other regulations REACH Status** The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH. **United States inventory** All components are listed or exempted. (TSCA 8b) All components are listed or exempted. Australia inventory (AICS) **Canada inventory** All components are listed or exempted. China inventory (IECSC) All components are listed or exempted. Japan inventory (ENCS) All components are listed or exempted. Korea inventory (KECI) All components are listed or exempted. **Philippines inventory** At least one component is not listed. (PICCS)

15.2	Chemical	Safety
Asse	essment	

This product contains substances for which Chemical Safety Assessments are still required.

# SECTION 16: Other information

Version 2 D	ate of issue 4	February 2014	Format	United Kingdom	Language	ENGLISH
Product name Ca	strol RR 363			Product code 450597	'-GB13	Page: 9/10
		Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS = Chemical Abstracts Service CLP = Classification, Labelling and CSA = Chemical Safety Assessmen CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DPD = Dangerous Preparations Dire DSD = Dangerous Preparations Dire EINECS = European Inventory of E ES = Exposure Scenario EUH statement = CLP-specific Haza EWC = European Waste Catalogue GHS = Globally Harmonized System IATA = International Air Transport A IBC = Intermediate Bulk Container IMDG = International Maritime Dang LogPow = logarithm of the octanol/v MARPOL 73/78 = International Con modified by the Protocol of 1978. ("I	Packagin t el ective [19 ctive [67/ xisting Co ard stater n of Class ssociatio gerous Go vater part vention fo	g Regulation [Regulation 99/45/EC] 548/EEC] ommercial chemical Su nent sification and Labelling n pods ition coefficient or the Prevention of Po marine pollution)	on (EC) No. 1 bstances of Chemicals llution From S	272/2008] hips, 1973 as
Abbreviations and acronyms	ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway ADR = The European Agreement concerning the International Carriage of Dangerous Goods by					

(UK)

(United Kingdom)

# **SECTION 16: Other information**

	OECD = Organisation for Economic Co-operation and Development PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SADT = Self-Accelerating Decomposition Temperature SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative		
Full text of abbreviated H statements	H302 H315 H318 H319 H373 (kidneys)	Harmful if swallowed. Causes skin irritation. Causes serious eye damage. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure if swallowed. (kidneys)	
Full text of classifications [CLP/GHS]	Acute Tox. 4, H302 Eye Dam. 1, H318 Eye Irrit. 2, H319 Skin Irrit. 2, H315 STOT RE 2, H373 (kidneys) (oral)	ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys) (oral) - Category 2	
Full text of abbreviated R phrases	R22- Harmful if swallowed. R41- Risk of serious damage R36- Irritating to eyes. R36/38- Irritating to eyes and		
Full text of classifications [DSD/DPD]	Xn - Harmful Xi - Irritant		
<u>History</u>			
Date of issue/ Date of revision	04/02/2014.		
Date of previous issue	05/11/2013.		
Prepared by	Product Stewardship		

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name	Castrol RR 363		Product code 45059	7-GB13	Page: 10/10
Version 2	Date of issue 4 February 2014	Format	United Kingdom (UK) (United Kingdom)	Language	ENGLISH